

Fuel Poverty Research Network (FPRN)

Research at the University of Salford's Energy House

David Farmer

Energy House Labs Research Fellow




University of Salford Energy House 1 Test Facility

- Salford Energy House (Energy House 1)
 - Replica of a pre-1920 end-terrace built using reclaimed materials and construction methods of its time
 - Over 200 permanent sensors monitoring energy and environmental conditions
 - Additional ~150 sensors installed for DEEP
 - Central heating system can be fed by either a boiler or air source heat pump
 - Automation of openings, appliance use, domestic hot water
 - Adjoining dwelling enables conditions in neighbour to be simulated
- Environmental chamber
 - Temperature range of -12°C to 30°C
 - Simulate wind, rain, and solar radiation
 - **Provides a repeatable test environment**






DEEP Retrofit Project

- DESNZ Demonstration of Energy Efficiency Potential (DEEP) Project
 - Collaboration with Leeds Beckett University and Loughborough University
- Energy House 1 provided a detailed **case study** investigating solid wall fabric retrofit thermal performance and its interaction with space heating systems
- Test aims:
 - Compare differences between piecemeal and whole house approaches to solid wall retrofit
 - Identify unintended consequences of fabric retrofit focusing on the risk of surface condensation and mould growth at junctions between elements
- Methodology:
 - Full fabric retrofit of the Salford Energy House following both approaches to fabric retrofit
 - Fabric thermal performance measurements throughout the retrofit process



Energy House DEEP Piecemeal Fabric Retrofit Programme

Test stage\Retrofit	Roof	Openings	Ground floor	External walls	Whole house approach measures
 Stage 1 - baseline	Cold roof - 100 mm mineral wool	'E' rated uPVC double glazing and doors	Suspended timber - uninsulated	225 mm brick with 12.5 mm wet plaster	Junctions untreated
 Stage 2 - roof	Additional 170 mm mineral wool. Total 270 mm mineral wool				
 Stage 3 - openings		'A' rated uPVC double glazing and GRP doors			
 Stage 4 - ground floor			150 mm mineral wool between joists + vapour barrier		
 Stage 5 - EWI [piecemeal approach full retrofit]		102 mm mineral wool external wall insulation (EWI)			


- Simulation of the piecemeal full fabric retrofit process
- Fabric thermal performance measurements at each test stage

Energy House DEEP Piecemeal Retrofit Measures

- Conventional retrofit materials
- Specified to meet Approved Document Part L1b
- Installation intended to simulate 'typical' practice











Energy House DEEP Piecemeal Approach to EWI



Energy House DEEP Whole House Approach Retrofit

Piecemeal retrofit approach retrofit

Whole house approach measures

Test stage\Retrofit	Roof	Openings	Ground floor	External walls	Whole house approach measures
 Stage 1 - baseline	Cold roof - 100 mm mineral wool	'E' rated uPVC double glazing and doors	Suspended timber - uninsulated	225 mm brick with 12.5 mm wet plaster	Junctions untreated
 Stage 2 - roof	Additional 170 mm mineral wool. Total 270 mm mineral wool				
 Stage 3 - openings		'A' rated uPVC double glazing and GRP doors			
 Stage 4 - ground floor			150 mm mineral wool between joists + vapour barrier		
 Stage 5 - EWI [piecemeal approach full retrofit]				102 mm mineral wool external wall insulation (EWI)	
 Stage 6a - EWI below DPC	EWI below DPC				
 Stage 6b - Bay window	Bay window roof, mullions, and sill externally insulated				
 Stage 6c - Extend eaves	Eaves extended to link loft insulation with EWI				
 Stage 6d - openings into EWI [whole house approach full retrofit]	Openings moved inline with EWI				

Conversion from piecemeal full retrofit to whole house approach full retrofit


Energy House DEEP Whole House Approach Measures

- EWI extended below DPC level
- Bay window roof, mullions, and sill insulated
- Eaves extended to link loft insulation and EWI
- Openings moved within the EWI



Energy House DEEP Surface Condensation and Mould Risk


- Pre-existing risk locations on front elevation:
 - External wall surfaces
 - Corner, eaves, and gable junctions
- EWI removed risk across wall surface and corner
- Extending eaves to link loft insulation with EWI removed risk at most eaves locations
- Residual risk at eaves/gable interface at verge due to difficulty installing insulation



Stage 2 – Loft retrofit





Stage 5 – EWI retrofit




Stage 6c – Eaves extended

Energy House DEEP Surface Condensation and Mould Risk


- Pre-existing risk locations on rear elevation:
 - External wall surface and junctions similar to front elevation
 - Window jamb and sill
- EWI + eaves extension had similar impact on both elevations
- EWI reduced risk around window reveals, notably on jambs
- Repositioning openings increased risk at some locations
- Work to reposition openings initially reduced airtightness
- Remedial sealing was required around reveals and thresholds



Stage 3 – ‘A’ rated glazing




Stage 6c – EWI + eaves extended




Stage 6c – Openings into EWI

Energy House DEEP Surface Condensation & Mould Growth Risk



- 9 baseline junctions considered a risk of surface condensation or mould growth
- 3 junctions remained a risk following piecemeal retrofit risk
- 1 junction remained a (medium) risk following whole house approach retrofit
- **Not all whole house measures were required** (e.g. repositioning of openings)

Energy House DEEP Retrofit Fabric Heat Loss and Cost



- Piecemeal approach full retrofit resulted in a 49% HTC reduction from baseline
- Whole house approach retrofit resulted in a 51% HTC reduction from baseline
 - Whole house approach measures increased cost of retrofit by ~50%
 - Some whole house measures could be considered unnecessary
 - **Whole house measures many not significantly reduce space heating energy bills**
- EWI resulted in a 44% HTC reduction from previous stage
 - Most effective HTC reduction measure, but also most costly
 - Most effective measure at removing risks at junctions



Energy House DEEP Fabric Testing Summary

- The whole house approach retrofit resulted in a lower risk of surface condensation and mould growth than the piecemeal retrofit
 - The fabric retrofit work required to minimise the risk of surface condensation cannot be financed through paybacks in space heating energy savings
 - Alternative funding models may be required
 - Some whole house measures were not required and added unnecessary cost to the retrofit
 - Survey tools that identify junctions that that require treatment will help specifiers decide which measures are appropriate and provide quality assurance of retrofits
- Existing piecemeal retrofits can be converted to whole house approach retrofits
 - Care needs to be taken not to damage existing thermal and airtightness barriers



Nesta – Boiler Flow Temperature

Salford Energy House Boiler Flow Temperature Testing

Initial Report

October 2022

University of Salford: David Farmer, Grant Henshaw, Ben Roberts, Professor Richard Fitton, Professor Will Swan

Heating consultant: Richard Burrows – Mid Wales Plumbing & Heating Supplies Limited



nesta



<https://www.nesta.org.uk/report/salford-energy-house-boiler-flow-temperature-testing-initial-report-october-2022/>




Nesta – Boiler Flow Temperature


Season	Flow temp. (°C)	Change in gas use		Change in boiler efficiency (% points)		Living room cycle temp. (°C)	Heat-up time (mins)	
		70 °C baseline	80 °C baseline	70 °C baseline	80 °C baseline		AM	PM
Winter	80	+5%	-	-1	-	21.0	23	24
Winter	70.2	-	-5%	-	+1	20.7	30	31
Winter	60.8	-7%	-12%	+4	+5	20.3	37	41
Winter	55.1	-12%	-16%	+5	+6	20.0	56	59
Winter	48.2	-19%	-23%	+5	+6	19.6	-	157
Shoulder	70.4	-	-	-	-	20.8	22	20
Shoulder	55.7	-13%	-	+3	-	20.4	20	21

- **Important** to note that gas central heating systems are typically designed for flow temperatures of 70 °C and reducing low temperature can:
 - Increase heat-up times
 - Impact thermal comfort
 - Resulting in failure to achieve set-point in cold conditions.
- Weather compensation control automate this process and can reduce space heating energy use and maintain set-points IF installed and commissioned correctly.

BBSA – Window Blind Testing



BBSA – Window Blind Testing



- Up to 37% reduction in centre pane U-value
 - Baseline of no window covering
 - 27% reduction from free hanging roller blind
- Generally, systems which were more airtight performed better
- Reduction in energy use will depend on glazing area and proportion of time spent with blinds closed

energyhouselabs.com



@Energy House Labs



@energyhouselabs1921

